

CLIENT:

JOB #:

COMPLETION DATE:

VEHICLE DETAILS:

FILM USED:

NOTES:



YOUR BRAND, EXPOSED.



FOLLOW US @292CREATIVE

HELLO@292CREATIVE.COM.AU

PHONE: 03 9457 9077

292CREATIVE.COM.AU

VEHICLE SIGNAGE, VINYL WRAP
& PAINT PROTECTION FILM
CARE & MAINTENANCE

BEFORE BRINGING IN YOUR VEHICLE

Please ensure the vehicle is relatively clean and that any existing signage, vinyl film, polishes and/or coatings have been removed.

If the vehicle is delivered dirty, there may be a surcharge to wash the vehicle & remove any existing vinyl so it is ready for application.

EXISTING CERAMIC COATINGS Paint protection film cannot be installed over any ceramic coating. If you're unsure if your vehicle has a ceramic coating applied, please contact the dealer where your vehicle was purchased or book in an appointment at our HQ for us to inspect.

STONE CHIPS & NON-FACTORY PAINT If your vehicle has pre-existing stone chips, paint damage or non-factory paint, there is a chance that there could be damage to the paint upon removal of paint protection film.

292 Co. Pty Ltd do not offer warranty and/or compensation should there be any damage to the paint surface upon removal or installation of the film.

WASHING YOUR WRAPPED VEHICLE

If you're taking your vehicle to a hand car wash, inform the car wash that your vehicle has been vinyl wrapped. Pressure washing may be used under the following conditions:

- Water pressure must be kept below 2000psi (14MPa).
- Keep water temperature under 35°C.
- Use 40° wide angle spray nozzle.
- Ensure nozzle is kept perpendicular to (90°) and at least 50cm from graphics or films.



DO NOT USE AUTOMATIC CAR WASHES OF ANY TYPE. The rotating brushes and extreme close proximity high-pressure hoses can damage the surface coating and cause edges to lift off or peel back. The use of automatic car washes will void all warranties from 292 and vinyl manufacturer.

VINYL WRAP, SIGNAGE, STRIPES & DECALS

MAINTENANCE GUIDELINES

To maintain vinyl wrap or vinyl decals, please follow this guideline:

Once you have washed your vehicle, it is recommend to apply a sealant to extend the longevity of the vinyl. We recommend Meguiar's Hybrid Ceramic Detailer or similar.

• The film should not be cleaned for 48 hours post application at the risk of altering its adhesion, which may result in the film lifting.

CAUTION Some cleaners, solvents and corrosive detergents could damage or alter the look of your wrap. 292 Co. Pty Ltd is not liable for any adhesive films cleaned with non-approved products.

Please contact us if you have any queries.

TIP Always be sure to test a small surface before proceeding with the cleaning of the entire wrap.

CAUTION In the event that fuel spills onto the film, wipe immediately to prevent degrading the vinyl surface or the adhesive (solvents may seep through and react with the adhesive).

STORAGE OF VEHICLE

Like automotive paint, vinyl film is affected by prolonged exposure to sun, wind, rain and pollutants (especially horizontal parts such as boots, roofs and bonnets). Wherever possible store vehicle under cover in a garage or use a protective car cover at night if storing outside.

If the vinyl film starts to fade or discolour this may be caused by acid rain or long exposure to UV. In this case we recommend removing the vinyl immediately to avoid damage to the body paint underneath.

PAINT PROTECTION FILM

MAINTENANCE GUIDELINES

To maintain the paint protection film, please follow this guideline:

- For the maintenance of your vehicle with Paint Protection Film, we recommend regular wash with PH neutral shampoo. **Solvents and corrosive detergents must not be used.**
- Don't wash or wax your vehicle for a minimum of 3 days following product installation.
- Regular wax or coating application every 6 months is recommended to help extend the life of the film.
- Do not use dyed or coloured car waxes on film.
- Remove insect or other stains as soon as possible.
- Use soft cloth or microfibre towels on film.
- Do not wipe or scrub the film in direct sunlight or when film is hot.
- Newly installed film takes 30 days to fully cure and there may be some haze or condensation.
- It is highly recommended you do not use any automatic car wash machines and only manually wash your vehicle.
- **Refer to "Washing your vehicle" in the Vinyl Wrap section of this brochure.**

MANUFACTURER WARRANTY

Zink Paint Protection Film offers a Limited 10 years warranty on all their products. This includes Gloss PPF, Matte PPF, Black PPF & Tinted PPF. Warranty starts from the date of initial installation. Warranty will cover defects film such as: yellowing, cracking, blistering and delaminating. 292 Co. Pty Ltd offers a 1 year workmanship warranty, see "warranty" below.

WARRANTY COVERAGE

292 Co. Pty Ltd offers a 1 year* workmanship warranty on all vehicle signage, vinyl wrap & paint protection film projects. Throughout the 1 year, you are welcome to book in an appointment at our HQ where we will be able to assess the defects and provide a solution. Additionally our material manufacturers warrant films against various conditions, this warranty depends on the product chosen.

As per the above storage guidelines, 292 Co. Pty Ltd will not offer any warranty or compensation against any wrap film or paint protection film damaging the car paint upon removal or at any stage.

For more information or a product data sheet please contact our team.
Ph: 03 9457 9077 or hello@292creative.com.au

* Warranty is only valid if client maintains the health of the vinyl wrap. We reserve the right to deny any warranty claim if we deem that the client has not followed the correct instructions as per the information in this brochure.

PPF DISCLAIMER

- Vehicles are cleaned using a pH Neutral Wash & Surface Cleaner & inspected for any paint imperfections & stone chips which are then noted for our reference.
- If there are any major imperfections in the vehicle paint, the customer is notified on how they wish to proceed.
- Precut templates are never perfect and may be slightly misaligned as film is stretched onto each panel. Therefore trimming on the vehicle may occur if film is slightly misaligned.
- Generally some trimming is required in the finishing process of installation. This requires the professional and careful use of a black to score the face of the film to trim back.
- Due to being a wet applied film some application marks, bubbles and or marks can appear. Majority of these issues tend to disappear after around 2 weeks.
- We recommend that all vehicles with paint protection film applied return to 292 Co. Pty Ltd 2 weeks after application for an inspection. In this inspection we will address any areas of concern before further damage occurs.
- Minor imperfections in the film cannot be avoided due to some installation difficulties.
- Being a clear film and a manual install job, there is always a chance of minor dust or particles that may appear under the film.